

SIGNET ARMORLITE – PROGRESSIVE LENS TECHNICAL SUMMARY

Signet Armorlite, Inc.

KODAK Lens

Semi-Finished Progressive Lenses	Vision Council Lens Specifications							
	LRP In	LRP Down	PRP Out	PRP Up	Drop	Inset	Corridor Lengths	Min. Fit Height
KODAK Precise® Lenses	3.0	-4.0	0.0	-4.0	4.0	3.0	17mm	17mm
KODAK Precise Short Lenses	3.0	-4.0	0.0	-4.0	4.0	3.0	13mm	13mm
KODAK Concise® Lenses	2.7	-2.0	-0.3	-2.0	2.0	3.0	14mm	14mm
Navigator®	2.2	-2.0	-0.3	-2.0	2.0	2.5	18mm	20mm
Navigator Short	2.7	-2.0	-0.3	-2.0	2.0	3.0	14mm	14mm
Shoreview™ ES *	2.5	-4.00	0.0	-4.0	4.0	2.5	18mm	18mm
Shoreview Mini ES *	2.5	-4.00	0.0	-4.0	4.0	2.5	15mm	15mm

Add Range: +1.00 to +3.00 in 0.25 D steps / *+0.75 to 3.50 in 0.25 D steps

Signetek™ Freeform Progressive Lenses	Vision Council Lens Specifications							
	LRP In	LRP Down	PRP Out	PRP Up	Drop	Inset	Corridor Lengths	Min. Fit Height
KODAK Unique DRO® /DRO HD Lenses	3.0	-4.0	0.0	-4.0	4.0	Variable	13, 14, 15, 16, 17, 18mm	13mm
KODAK Unique™ /HD Lenses	3.0	-4.0	0.0	-4.0	4.0	Variable	13, 14, 15, 16, 17, 18mm	13mm
KODAK Precise® Plus Lens	3.0	-4.0	0.0	-4.0	4.0	3.0	13mm	13mm
KODAK Precise Short Plus Lens	3.0	-4.0	0.0	-4.0	4.0	3.0	17mm	17mm
KODAK Precise PB Lenses	3.0	-4.0	0.0	-4.0	4.0	3.0	17mm	17mm
KODAK Precise Short PB Lenses	3.0	-4.0	0.0	-4.0	4.0	3.0	13mm	13mm
KODAK Easy / 18mm	3.0	-4.0	0.0	-4.0	4.0	3.0	18mm	18mm
KODAK Easy / 14mm	3.0	-4.0	0.0	-4.0	4.0	3.0	14mm	14mm
DirecTek™ Lenses	3.0	-4.0	0.0	-4.0	4.0	3.0	16.5mm	16.5mm
DirecTek Short Lenses	3.0	-4.0	0.0	-4.0	4.0	3.0	13.5mm	13.5mm
Navigator® FBS Lenses	3.0	-4.0	0.0	-4.0	4.0	3.0	18mm	18mm
Navigator Short® FBS Lenses	3.0	-4.0	0.0	-4.0	4.0	3.0	14mm	14mm
KODAK SoftWear™ Lenses* (Computer) <i>(previously KODAK MonitorView™ Lenses)</i>	3.0	-2.0	0.0	-2.0	2.0	3.0	14mm	17mm

Add Range: +0.75 to +3.50 in .25 D steps

**KODAK SoftWear Lenses are not progressive lenses and devote a majority of the viewing to the near and intermediate distances.*

The inset is the horizontal decentration of the lens design. (The distance from the geometric center of the lens blank to the prism reference point.)

Corridor length is the distance in millimeters from the fitting cross to the full add power.

The fitting or seg height is the measurement from the fitting cross to the lowest bottom edge of the lens (Must consider lens shape i.e. right triangle).

The drop is the distance (mm) from the center of the fitting cross to the PRP.