

KODAK CleAR FSV 1.67

Technical Data

POWER	DIAMETER	FRONT CURVE	EDGE THICKNESS	CENTER THICKNESS								
				0.00	-0.25	-0.50	-0.75	-1.00	-1.25	-1.50	-1.75	-2.00
-2.00	75	2.79	3.5	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
-2.25	75	2.99	3.7	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
-2.50	75	2.79	4.0	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
-2.75	75	2.60	4.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
-3.00	75	2.39	4.5	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
-3.25	75	2.61	4.8	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
-3.50	75	2.41	5.1	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
-3.75	75	2.21	5.4	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
-4.00	75	2.02	5.6	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
-4.25	75	2.21	6.0	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
-4.50	75	2.02	6.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
-4.75	75	1.82	6.5	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
-5.00	75	1.62	6.8	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
-5.25	75	2.21	7.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
-5.50	75	2.02	7.5	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
-5.75	75	1.82	7.7	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
-6.00	75	1.62	8.0	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
-6.25	70	1.82	7.3	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	
-6.50	70	1.63	7.5	1.2	1.2	1.2	1.2	1.2	1.2	1.2		
-6.75	70	1.43	7.7	1.2	1.2	1.2	1.2	1.2	1.2			
-7.00	70	1.23	8.0	1.2	1.2	1.2	1.2	1.2				
-7.25	70	1.82	8.4	1.2	1.2	1.2	1.2					
-7.50	70	1.63	8.6	1.2	1.2	1.2						
-7.75	70	1.43	8.8	1.2	1.2							
-8.00	70	1.23	9.1	1.2								